



# Installation Instructions

## FLUIDAMPR 651201

1. Put front clip into service position.
2. Loosen automatic tensioners with 3/8" drive breaker bar.
3. Carefully slip belts off of damper.
4. Note the location of the offset hole marked with two spot faces.
5. Remove bolts and OE damper from engine. The damper may need to be walked off side to side if corrosion is present.
6. Inspect crank flange for damage or buildup. Remove buildup if found.
7. With the offset hole aligned, slide Fluidampr 651201 onto crankshaft flange.
8. Install supplied M8-1.25x30mm bolts and torque to 27 N-m (240 in-lbs).
9. Reinstall belts according to factory belt routing. Use 3/8" breaker bar to release tensioners for re-installation.
10. Place vehicle in neutral (manual transmissions) or park (automatic transmissions) and start engine. Carefully check for damper wobble or belt misalignment, if found, recheck installation and damper seating.
11. Place front clip back into operating position.

### Warranty

WARRANTY: All warranty claims must be made with your point of purchase. LIMITED WARRANTY: Fluidampr warranty extends to the original purchaser only and a copy of sales receipt must be provided. Keep your receipt. Fluidampr recommends to our customers that they have their Fluidampr products installed by a certified technician or engine builder as warranty does not cover installation errors. Fluidampr offers a 1 year warranty for defects in material and workmanship. Repair or replacement will be at Fluidampr's discretion. If purchased from Fluidampr: To obtain warranty service, call customer service to receive a return authorization number. Returns must include the RMA#, description of the problem and a copy of the purchase invoice/receipt. Returns without an RMA# will not be processed. Customers are responsible for freight charges to Fluidampr. If product is found to be faulty, Fluidampr will pay UPS Ground Freight when returning the product to customer. THIS WARRANTY DOES NOT INCLUDE AND IS NOT LIMITED TO THE FOLLOWING: • Failure due to improper installation or maintenance. Loss or injury incurred from use or operation of Vibratech/Fluidampr products. • Misuse, abuse, modifications, or unauthorized repairs. • Removal or replacement cost. • Cost incurred due to downtime of vehicle. • Damage to other engine or vehicle components. • Normal wear and tear. • Use in racing applications or competitive purposes. Fluidampr limited warranty coverage is subject to change due to uncontrolled circumstances with or without notice.

Vibratech/Fluidampr • 180 Zoar Valley Rd • Springville, NY 14141 • PHONE 716-592-1000 • FAX 716-592-1001

• Website: [www.fluidampr.com](http://www.fluidampr.com) • E-mail: [support@fluidampr.com](mailto:support@fluidampr.com)

Printed in USA

P/N 4NFV04

Revised 10/2019